

Sunmi Scanner

geidea

HANDHELD SCANNER

FEATURES

- Quick scanning
- Accurate Identification
- Haptic Feedback
- Exceptional Code Identification
- Dual light
- Supports 1D/2D Bar Codes
- Shake-Proof & Impact-Proof
- Vibrating Alert
- Multiple system compatibility

High-performing, fast and accurate multi-purpose code scanner.



FEATURES



Barcode
Scanning



Mobile
Payment



















Drop-Proof



Plug and Play

TECHNICAL SPECIFICATIONS

 OS Windows/iOS Android/Linux	 IMAGE SENSOR CMOS	 PIXEL 640*480	 READING PRECISION ≥3mil	 CODE RECOGNITION SYSTEM 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand 2D : PDF417, QR Code, Data Matrix
 READING DEPTH OF FIELD EAN13 (13mil) 55mm-300mm QR CODE (15mil) 35mm-190mm	 LIGHTING White LED	 ADAPTER Operating voltage: DC5V±5% Operating current: <500mA	 PROMPT METHOD Buzzer, vibrator, LED prompt	
 FOCUSING Red light LED 625nm	 BARCODE SENSITIVITY Inclined ±50° / Rotary 360° / Deflected ±50°	 FIELD OF VIEW ANGLE Horizontal 45° Vertical 34°		 ENVIRONMENT Operating temperature: -10°~50° Storage temperature: -40°~70° Relative humidity: 5%~95% (no condensation) Electrostatic protection: ±8kV (direct discharge) ±15kV (air discharge) Drop height: 1.2 meters
 SYMBOL CONTRAST ≥30%	 SIZE 160mm*95mm*71mm	 PORT 1× USB Type-A		