

Pro Cash Drawer



✓ SAME CAPACITY, LESS SPACE.

Features:

- Sleek design
- Wide area voltage
- Durable, long service life
- Unique security features
- Industrial bearing mechanism for solid and smooth usage
- Open drawer with the press of a finger
- Cable storage compartment on top
- Strengthened steel metallic clips covered by durable ABS for noise reduction
- Suitable for 9V/12V/24V cash register output voltage



FEATURES



10Kg
bearable



1,000,000+
operations



Open
interfaces



Customizable
safety reminder



Three positions
lock design

Pro Cash Drawer



TECHNICAL SPECIFICATIONS



CASH DRAWER

Plastic and metallic



TRAYS

Four normal bill & one big bill trays
Three coin trays



METALLIC BEARING

Up to 10kg bearable



CABLE

RJ12, 6P4C, 0.8m



LOCK

Three positions lock
(electronic, manual and deadlock)



BILL CLIP

Plastic and metallic



CABLE STORAGE COMPARTMENT

Rear-set compartment with cover



DRIVE VOLTAGE

DC9V~24V, 1A



DRIVE PULSE WIDTH

100ms - 300ms



DRIVE PROTECTIONS

3A overcurrent protection
triggered by electromagnetic
valve shrot circuit
Input pulse overvoltage
protection
Input pulse timeout protection
Self-adaptive to 9V-28V input
voltage
Contact ESD 8KV/air ESD 15KV
Termal shutdown



SERVICE LIFE

≥1000000 operations



NOISE

<50dB



STATUS FEEDBACK

Status detection
switch



WORKING ENVIRONMENT

Working temperature and humidity:
0° ~ 45°, 30% ~ 85%
Storage temperature and humidity:
-20° ~ 60°, 10% ~ 90%



WEIGHT

2.3 Kg



SIZE

W317mm x L332mm x H72mm

Call or email to
find out more

920011422
support@geidea.net

geidea.net

