

# Pro Scanner



## **HANDHELD SCANNER**

Fast and accurate scanning that efficiently handles busy checkout points.

### Features:

- Quick scanning
- Accurate Identification
- Haptic Feedback



**FEATURES**



Barcode  
Scanning



Mobile  
Payment



















Drop-Proof



Plug  
and  
Play

## TECHNICAL SPECIFICATIONS

 <b>OS</b> Windows/iOS Android/Linux	 <b>IMAGE SENSOR</b> CMOS	 <b>PIXEL</b> 640*480	 <b>READING PRECISION</b> ≥3mil	 <b>CODE RECOGNITION SYSTEM</b> 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand 2D : PDF417, QR Code, Data Matrix
 <b>READING DEPTH OF FIELD</b> EAN13 (13mil) 55mm-300mm QR CODE (15mil) 35mm-190mm	 <b>LIGHTING</b> White LED	 <b>ADAPTER</b> Operating voltage: DC5V±5% Operating current: <500mA	 <b>PROMPT METHOD</b> Buzzer, vibrator, LED prompt	
 <b>FOCUSING</b> Red light LED 625nm	 <b>BARCODE SENSITIVITY</b> Inclined ±50° / Rotary 360° / Deflected ±50°	 <b>FIELD OF VIEW ANGLE</b> Horizontal 45° Vertical 34°		 <b>ENVIRONMENT</b> Operating temperature: -10°~50° Storage temperature: -40°~70° Relative humidity: 5%~95% (no condensation) Electrostatic protection: ±8kV (direct discharge) ±15kV (air discharge) Drop height: 1.2 meters
 <b>SYMBOL CONTRAST</b> ≥30%	 <b>SIZE</b> 160mm*95mm*71mm	 <b>PORT</b> 1× USB Type-A		

Call or email to  
find out more

**920011422**  
**support@geidea.net**

**geidea.net**

